WAGNER
REINHARDT-TECHNIK

Dynamic Mix 3.0

Up to € 15,000.- savings of operating expenses **per year** possible*

DYNAMIC MIXER WITH **DISPOSABLE MIXING CHAMBER** AND **TWO COMPONENT SWIVEL JOINT** FOR INTEGRATION INTO **MANUAL SEALING PLANTS**



BENEFITS

- Freezer or solvent flushing pump no longer required
- No more loss of material through purging processes
- Saving of costs for disposal of waste material**
- No more necessity for cleaning of Z-swivel joint
- No purchase of trompet mixer required
- Less attrition of the plant by lowering the pressure level to approximately 120 bar

	Dimensions	Length	Width	Height
		700 mm	150 mm	200 mm
	Admissive operating pressure	450 to 1,000 cm³/min		
	Maximum dyn. operating pressure	200 bar		
	Max. air pressure	6 bar		
	Weight	4,350 g		

PERFECT MATCH WITH **ECOSTAR EVO**

Optionally available as integrated in Ecostar evo-series or as retro-fit kit for existing installations.

*Depends on material and production parameters

מכניק א.ג.ר בע"מ
MECHANIK A.G.R. LTD
مكنيك أ.ج.ر.

WAGNER GROUP

WAGNER
REINHARDT-TECHNIK

מכניק א.ג.ר בע"מ
MECHANIK A.G.R. LTD
مكنيك أ. ج.ر .



YOUR GLOBAL PARTNER IN

METERING AND MIXING TECHNOLOGY

- Processing and application of single and multi component adhesive and sealants
- Ambient or temperature conditioned equipment
- Complete systems for manual or fully automatic processes
- Innovative process control and verification

מכניק א.ג.ר בע"מ
MECHANIK A.G.R. LTD
مكنيك أ. ج.ر .

Reinhardt-Technik GmbH
Waldheimstraße 3
58566 Kierspe/Germany
T +49 (0)2359 666 - 0
F +49 (0)2359 666 - 129
info-rt@wagner-group.com
www.reinhardt-technik.com

WAGNER GROUP

Rev.-Nr.: DM - 1409 - 002 - EN - Item no.: 2373353